



**Cimar**<sup>®</sup>  
produzione s.u.r.l.

Via Mecio Gracco 8H/I - 84131 Salerno IT  
Tel/Fax +39 089 302418 - info@cimarproduzione.com  
www.cimarproduzione.com

PRIMER 70 metri SILVER (Bituminous Primer)

TECHNICAL DATA SHEET

PRIMER 70 metri SILVER (Bituminous Primer)

Date of revision 20.09.22

#### 1. IDENTIFICATION OF THE SUBSTANCE/COMPANY

Trade name : PRIMER 70 meters SILVER (Bituminous primer)  
Additional name : Bituminous primer based on distilled bitumen and fast-drying regenerated solvents.  
Manufacturer : Cimar Produzione Surl with plant in Salerno at 8H/8I Mecio Gracco Street.  
Telephone number also for urgent calls: Tel +39 089.302418

#### 2. CHARACTERISTICS AND USES

Primer 70 meters SILVER is a high-penetration adhesion promoter for bituminous waterproofing materials such as prefabricated membranes, bituminous liquid membranes and hot bitumen. The product consists of bitumen in solution with pure solvents that is fast drying and adheres to any surface.  
Primer 70 M SILVER can also be used as a waterproofing agent for vertical wall surfaces and in the protection of wooden structures, pipes and metal structures, both exposed and buried.

#### 3. LIQUID PRODUCT IDENTIFICATION CHARACTERISTICS

Appearance: Glossy black liquid  
Specific gravity =  $0.9 \pm 0.05 \text{ kg/dm}^3$   
Dry residue = 45-50 %  
VOC content as per Legislative Decree dated 27/05/2006 No. 161: 750 g/l ready-to-use product  
VOC content in the product: 650 g/l ready-to-use product  
UFI: 2P00-003G-Q009-Y2V7

#### 4. DRYING OR CURING AT 23°C AND 50% UR

On the surface: 10 min  
To the touch: 20 min

#### 5. EQUIPMENT

Apply by brush, roller, brush or spray (airless).

#### 6. APPLICATION SUPPORT

Clean and dry surfaces.

#### 7. DILUTION

Ready to use

#### 8. CONSUMPTION

Consumption depends on the porosity and regularity of the surface to be treated. It normally ranges from 100-300 g/sqm depending on the surface.

## 9. INDICATIONS FOR STORAGE

Store in a dry and well-ventilated place in its closed containers away from open flames and heat sources.  
Stability in original packaging : 12 months  
Packaging : 5 lt - 10 lt - 18 lt

## 10. COLORS AND WARNINGS

Black

Do not use flame on product that is not perfectly dried.

Flammable product.

Apply the product on perfectly dry substrates.

Carry out thorough cleaning of the surface to be treated, removing dust, loose crumbly parts, grease, oils and anything else that may affect the anchorage of the product to the substrate.

Strictly adhere to the expected consumption quantities, assess the porosity of the substrate since the use of quantities greater than those necessary, determines problems of drying of the product, jeopardizing the adhesion of the next product.

Read the safety data sheet carefully before using it.

*The information contained in this prospectus is, to the best of our knowledge, exact and accurate, but any recommendations and suggestions given are without warranty, as the conditions of use are not under our direct control. In case of doubt, it is always advisable to make preliminary tests and/or ask for the intervention of our technicians. The company Cimarrone Produzione srl reserves the right to modify, replace and/or eliminate items, as well as vary the data of the products given in this prospectus, without prior notice; in this case the indications given here may no longer be valid.*